IP CAMERAS

EOS IBS-401RS/DUAL

4MP Dual Illumination IP bullet camera · Code 8041119 · App: CybVu

An affordable 4MP camera that gives you a picture day and night: infrared in the dark and white light for color video as soon as motion is detected. A single PoE cable powers it.

4MP · Dual Illumination · Colour at night · Audio · PoE · IP66 · ONVIF · Human detection

4 MP resolution

96° horizontal view

25 m infrared

IP66 outdoor rated

KEY FEATURES

- 4 MP (2560×1440) at 25 fps
- Dual illumination: 25 m infrared and 20 m white light
- Smart detection of people, line crossing and intrusion
- Wide 96° view with a 2.8 mm lens
- Built-in microphone
- PoE powered, IP66 plastic housing

SPECIFICATIONS

Image	
Sensor	**1/3" CMOS**
Resolution	**4 MP (2560×1440) @ 25 fps**
Compression	**H.265, H.264, dual stream**
Lens	**2.8 mm (fixed)**
Field of view	**96° horizontal, 52° vertical, 113° diagonal**
Image enhancement	**BLC, HLC, DWDR, 3DNR, Defog**

Lighting & night vision	
Sensitivity	**Color 0.004 lux @ F1.6 (AGC ON) · B/W 0 lux with IR**
Infrared (IR)	**up to 25 m**
White light	**up to 20 m**
Night mode	**Black & white with IR; on motion or intrusion the white light turns on for color video**

Smart functions	
Detection	**Smart motion detection with human detection, area intrusion, line crossing, region entry/exit**

Network & recording	
Protocols	**TCP/IP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP**
Compatibility	**ONVIF**
Recording	**NVR, CMS software**
App	**EOS Vision**
Viewing	**PC, Android, iPhone, iPad**
Web server	**Built-in (view in a browser)**
Multiple users	**Simultaneous connections**

Audio	
Audio	**Built-in microphone**

Power & construction

Power	**PoE (IEEE 802.3af)**
Power consumption	**3.28 W**
Protection	**IP66**
Housing	**Plastic**
Dimensions	**Ø70 × 150 mm**
Weight	**295 g**
Color	**White**
Operating temperature	**−35 to +55 °C**