

EOS IDS-400RS/AD

4MP Active Deterrence IP dome camera · Code 8041112 · App: CybVu

When it spots a person, it flashes red and blue lights and sounds a siren, so the intruder knows you are watching. At the same time you get color video and an alert on your phone.



4MP

Active Deterrence

Dual Illumination

Colour at night

Audio

PoE

IP66

ONVIF

Human detection

4 MP

resolution

0.002 lux

color video

25 m

infrared

IP66

outdoor rated

KEY FEATURES

- 4 MP (2560×1440) at 25 fps
- Red/blue lights and siren on smart detection
- 25 m infrared and 20 m white light
- Color video down to 0.002 lux
- Built-in microphone and speaker
- 12 VDC or PoE power, IP66 rated

SPECIFICATIONS

Image

Sensor	1/3" CMOS
Resolution	4 MP (2560×1440) @ 25 fps
Compression	H.265, H.264, dual stream
Lens	2.8 mm (fixed)
Field of view	78° horizontal, 42° vertical, 92° diagonal
Image enhancement	BLC, HLC, DWDR, DNR

Lighting & night vision

Sensitivity	Color 0.002 lux @ F1.6 (AGC ON) · B/W 0 lux with IR
Infrared (IR)	up to 25 m
White light	up to 20 m
Night mode	Black & white with IR; on motion or intrusion the white light turns on for color video
Active deterrence	Red and blue lights and siren, triggered by smart detection

Smart functions

Detection	Smart motion detection with human detection, area intrusion, line crossing, region entry/exit
-----------	---

Network & recording	
Protocols	TCP/IP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, P2P
Compatibility	ONVIF
Recording	NVR/DVR, CMS software, SD card
App	EOS Vision (free), P2P with QR code scan
Viewing	PC, Android, iPhone, iPad
Web server	Built-in (view in a browser)
Multiple users	Simultaneous connections

Audio	
Audio	Built-in microphone and speaker
Power & construction	
Power	12 VDC or PoE (IEEE 802.3af)
Power consumption	5 W
Protection	IP66
Dimensions	Ø100 × 90 mm
Weight	330 g
Color	White
Operating temperature	−35 to +60 °C