

EOS IDS-401RS/DUAL

4MP Dual Illumination IP dome camera · Code 8041120 · App: CybVu

An affordable 4MP camera that gives you a picture day and night: infrared in the dark and white light for color video as soon as motion is detected. A single PoE cable powers it.



4MP

Dual Illumination

Colour at night

Audio

PoE

IP66

ONVIF

Human detection

4 MP

resolution

96°

horizontal view

25 m

infrared

IP66

outdoor rated

KEY FEATURES

- 4 MP (2560×1440) at 25 fps
- Dual illumination: 25 m infrared and 20 m white light
- Smart detection of people, line crossing and intrusion
- Wide 96° view with a 2.8 mm lens
- Built-in microphone
- PoE powered, IP66 plastic housing

SPECIFICATIONS

Image

Sensor	1/3" CMOS
Resolution	4 MP (2560×1440) @ 25 fps
Compression	H.265, H.264, dual stream
Lens	2.8 mm (fixed)
Field of view	96° horizontal, 52° vertical, 113° diagonal
Image enhancement	BLC, HLC, DWDR, 3DNR, Defog

Lighting & night vision

Sensitivity	Color 0.004 lux @ F1.6 (AGC ON) · B/W 0 lux with IR
Infrared (IR)	up to 25 m
White light	up to 20 m
Night mode	Black & white with IR; on motion or intrusion the white light turns on for color video

Smart functions

Detection	Smart motion detection with human detection, area intrusion, line crossing, region entry/exit
-----------	---

Network & recording

Protocols	TCP/IP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP
Compatibility	ONVIF
Recording	NVR, CMS software
App	EOS Vision
Viewing	PC, Android, iPhone, iPad
Web server	Built-in (view in a browser)
Multiple users	Simultaneous connections

Audio

Audio	Built-in microphone
-------	---------------------

Power & construction

Power	PoE (IEEE 802.3af)
Power consumption	3.28 W
Protection	IP66
Housing	Plastic
Dimensions	Ø99 × 86.9 mm
Weight	263 g
Color	White
Operating temperature	-35 to +55 °C