

POWER & UPS

EOS MINI DC36W-LCD

Mini DC UPS 36 W with PoE and LCD display · Code 6253023

Keep IP cameras, routers and switches running when the power goes out. A PoE output, three DC outputs and USB let you power what you need from one unit.



PoE

Battery

LCD display

36 W

max output

10,400 mAh

battery

15/24 V

PoE output

5/9/12 V

DC outputs

KEY FEATURES

- 3 DC outputs: 5 V, 9 V and 12 V, plus a USB output
- PoE output, selectable 15/24 VDC, plus a LAN port
- LCD shows battery capacity and output voltage
- 10,400 mAh battery, 36 W maximum output
- Overcharge, over-discharge, overvoltage and short-circuit protection
- Starts automatically when connected to power

SPECIFICATIONS

Input & outputs

Input	85–265 VAC, 50/60 Hz
DC outputs	1× 5 V, 1× 9 V, 1× 12 V
USB	1× USB output
PoE	1× PoE 15 VDC / 24 VDC (selectable)
LAN	1× LAN port
Max output power	36 W

Battery & protection

Battery	10,400 mAh (4× 2,600 mAh)
Control	Microprocessor
Protection	Overcharge, over-discharge, overvoltage, short circuit
Display	LCD, battery capacity and output voltage
Buttons	On/Off, Reset, PoE 15 V / 24 V selector
Start-up	Automatic when connected to power

Build & environment

Operating temperature	0 to +40 °C
Operating humidity	10–90% RH
Dimensions	180 × 106 × 40 mm
Weight (gross)	659 g
Colour	Black

IN THE BOX

Mini DC UPS · Power cable 0.8 m · DC to DC cable (5.5 × 2.5), 0.3 m · DC to 2× DC cable (5.5 × 2.5), 0.3 m · User manual